

# Zero Smog 2 Kit 2 Nozzle

Code No.: FT91007699N



## Benefits

- › Easy filter exchange
- › Quick and simple installation
- › Portable fume extraction unit
- › The fume extraction unit Zero Smog 2 is easy to install and operate. It is designed as a small, economical central system for two workplaces. The Kit 2 nozzle consist of the ZS 2 extraction unit, 2 flexible extraction arms 1,5 Meter with table clamp and 2 sloped nozzles. The system for two workplaces is easy to install by placing the unit at the bench. Both extraction arms will adapt direct on the unit and can fix with a clamp at the bench.


In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables




Preheating plates



**Technical Data**

|                                  |   |
|----------------------------------|---|
| Dimensions W x D x H (mm)        | 360 x 330 x 415                           |
| Dimensions W x D x H (Inch)      | 14,17 x 12,99 x 16,33                     |
| Weight (ca) in kg                | 9   |
| Voltage                          | 220-240 V (50/60 Hz)                      |
| Heating output                   | 185VA                                     |
| Noise level (distance 1 m) dB(A) | < 53                                      |
| Max. vacuum                      | ---                                       |
| Capacity m <sup>3</sup> /h       | 190                                       |
| Pre filter                       | Pre filter mat class M5                   |
| Cartridge Volume Extraction      | Particle filter H13, Active carbon filter |
| Max. capacity                    | 1-2 workplaces                            |
| Interface RS232 (Remote control) | ---                                       |
| USB interface                    | ---                                       |
| WX compatible                    | ---                                       |

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE