

WFE Fume extraction unit

Code No.: T0053640299N




Benefits

- › Maintenance free compressed air converter
- › For industrial long term use
- › Up to 2 FE soldering irons can be connected
- › High stability against overturning
- › A compressed air cleaning filter removes additional odours caused by the compressed air.
- › The fume extraction unit WFE requires clean and oil-free compressed air. The vacuum is generated by a maintenance-free compressed air converter. The contaminated air is purified by a pre-filter and main filter system. A compressed air cleaning filter removes additional odours caused by the compressed air. This highly efficient filter system makes the WFE a genuine air recovery system. The FE (Fume Extraction) soldering irons are connected directly to the unit – additional leads are not required.


In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables




Preheating plates



Technical Data

Dimensions W x D x H (mm)	140 x 140 x 200
Dimensions W x D x H (Inch)	5,51 x 5,51 x 7,87
Weight (ca) in kg	2.7
Voltage	---
Heating output	6 bar
Operating pressure	3,5 - 6,0 / 50 - 90
Air consumption l/min	30
Noise level (distance 1 m) dB(A)	< 39
Max. vacuum	20.000
Max. capacity	2 workplaces
Pre filter	Pre filter mat class F7
Cartridge Volume Extraction	Particle filter H13, Wide band gas filter (50 % Active carbon + 50 % Chemisorb)

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE