

WXR 3

3-Channel Power Unit, 420 W (600 W)
Code No.: T0053500699N



Benefits

- > All-in-one-Station
- > Benchtop controller capability e.g. Zero Smog Systems
- > Automatic tool recognition and power management
- > Compatible with all WX tools
- > Storage medium in hand piece
- > Blue LED backlighting
- > Multilingual menu navigation

In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables



Preheating plates



Technical Data

Dimensions W x D x H (mm)	273 x 235 x 102
Dimensions W x D x H (Inch)	10,75 x 9,25 x 4,02
Weight (ca) in kg	6.7
Voltage	230 V (50/60 Hz)
Power output	420 W (600 W)
Channels	3
Temperature range (depends on tool) °C	100 - 450 (550)
Temperature range (depends on tool) °F	200 - 850 (999)
Temperature accuracy °C	±9
Temperature accuracy °F	±17
Temperature stability °C	±2
Temperature stability °F	±4
Equipotential bonding	Via 3.5 mm pawl socket on back of device (Hard grounded)
Display	255 x 128 dots / Backlighting
Air consumption l/min	---
Operating pressure	---
Capacity l/min	18, max.
Vacuum	---

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE