
6966 EK Hot air heat gun Hot air heat gun 250 W / 230 V Code No.: 6966EK



In addition we recommend:







Soldering Irons



Cleaning Consumables



Preheating plates

Weller



| Dimensions W x D x H (mm) Dimensions W x D x H (Inch) 8,66 x 3,35 x 9,84 Inch Weight (ca) in kg Voltage Voltage 230 V (50 Hz) Power output Channels Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C toda 220 x 85 x 250 mm 8,66 x 3,35 x 9,84 Inch 0,57 kg Voltage 230 V (50 Hz) 210 W Channels Temperature range (depends on tool) °C Temperature accuracy °C tbd | |
|--|--|
| Weight (ca) in kg Voltage 230 V (50 Hz) Power output Channels Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F tod tod 0,57 kg 230 V (50 Hz) 210 W 425 425 797 797 tod tbd | |
| Voltage 230 V (50 Hz) Power output 210 W Channels Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C tbd Temperature accuracy °F | |
| Power output 210 W Channels Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °C tbd Temperature accuracy °F | |
| Channels Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F tbd | |
| Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F tbd | |
| on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F tbd | |
| on tool) °F Temperature accuracy °C tbd Temperature accuracy °F tbd | |
| Temperature accuracy °F tbd | |
| | |
| Temperature stability °C tbd | |
| | |
| Temperature stability °F tbd | |
| Equipotential bonding | |
| Display | |
| Air consumption I/min | |
| Operating pressure | |
| Capacity I/min | |
| Vacuum | |

Owning the bench









Phone: +49 (0) 7143 / 580-0 Fax.: +49 (0) 7143 / 580-108 Email: info@weller-tools.com Web: www.weller-tools.com