

DATASHEET

Stainless Steel General Purpose Trolley

Description:

The serving trolleys are manufactured from high-quality stainless steel.

Rugged construction made from two tubular steel bar push handles, Ø 25 mm, with welded deep drawn shelves with elevated perimeter flange in-between. Deposit surface with large radii for easy cleaning, lowered by approx. 10 mm in contrary to the perimeter flange.

Shelves are bevelled by 35 mm all over, with flat safety return to the inside and sound absorbing lining. The trolley is protected from damage by four disc bumpers which are fixed directly above the castors. Disc bumpers are made from elastic and shock resistant plastic material. If necessary they can be exchanged easily by releasing the castors.

Corrosion-protected and maintenance-free castors. Housings made from zinc-chrome plated steel, solid castor made from impact-proof, accident grease-proof plastic, tyres from thermoplastic rubber. High-grade bearing by slide-bearings. 4 swivel castors, Ø 125 mm, 2 with brake.

If necessary the castors can be exchanged easily, pin fixing.

Optionally and for additional price the trolleys can also be equipped with 2 fixed and 2 swivel castors.

Features:

- Two shelves
- 304 grade stainless steel
- 40kg payload per shelf
- Overall dimensions: 895mm x 595mm x 960mm
- Shelf size 800mm x 500mm



Number of shelves:	2
Shelf dimensions in mm:	600 x 400
Load per unit area / shelf:	40kg
Working height between shelves in mm:	538
Height of top shelf in mm:	800
Chassis:	4 swivel castors, 2 of them with brake, Ø 125 mm
Total load capacity:	80kg
Net weight:	11kg
External dimensions W x D x H in mm:	695 x 495 x 892

Product Code:	Description:	Overall Size (inches):	Overall Size (mm):	Additional Notes:
612-0011	Stainless Steel General Purpose Trolley	35 x 23 x 38	895 x 595 x 960	Each