

# PUD 151R

Power unit, 1 channel, 150 W  
Code No.: T0053278670N



## Benefits

- › Temperature window adjustable  $\pm 99^{\circ}\text{C}$
- › Temperature control via buttons
- › 3-position digital display
- › Calibration unit WCB 2 connectable
- › Automatic tool recognition
- › Digitally controlled electronic for soldering tools upto 150 W

In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables



Preheating plates



**Technical Data**

Dimensions W x D x H (mm)	170 x 118 x 102 mm
Dimensions W x D x H (Inch)	6,69 x 4,65 x 4,02 Inch
Weight (ca) in kg	2,05 kg
Voltage	230 V
Power output	150 W
Channels	1
Temperature range (depends on tool) °C	50 - 550
Temperature range (depends on tool) °F	150 - 999
Temperature accuracy °C	± 11
Temperature accuracy °F	± 19
Temperature stability °C	± 5
Temperature stability °F	± 9
Equipotential bonding	Via 3,5 mm pawl socket on back of device (normal state hard grounded)
Display	LED
Air consumption l/min	---
Operating pressure	---
Capacity l/min	---
Vacuum	---

Owning the bench



PROFESSIONAL



FILTRATION



EREM



XCELITE