Weller*

WT 1H

1-Channel Power Unit, 150 W Code No.: T0053435699N





Benefits

- > High productivity (Power unit with 1 channel, 150W)
- > Intuitive use thanks to clear menu structure
- > Reduced footprint thanks to stackability
- Grafical backlit LC-Display
- High performance and functionality -many connectable tools
- Automatic standby of tool thanks to integrated acceleration sensor in the tool
- > Housing cover useable as storage
- > Lock function

In addition we recommend:



Fume extraction devices



Soldering Irons



Cleaning Consumables



Preheating plates



Dimensions W x D x H (Inch) Dimensions W x D x H (Inch) S.87 x 5.43 x 3.98 Weight (ca) in kg Voltage Power output Channels 1 Temperature range (depends on tool) °C Temperature accuracy °C Temperature accuracy °F Temperature stability °C Temperature stability °F Equipotential bonding 149 x 138 x 101 5.87 x 5.43 x 3.98 3 Voltage 3 230 V, 50 Hz 50 - 55 W 150 - 999	
Weight (ca) in kg Voltage 230 V, 50 Hz Power output 150 W Channels 1 Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C Temperature stability °F 150 - 999 150 -	
Voltage 230 V, 50 Hz Power output 150 W Channels 1 Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C Temperature stability °F Temperature stability °F	
Power output Channels 1 Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °C Temperature stability °C Temperature stability °F 150 W 10 10 10 10 10 10 10 10 10 1	
Channels 1 Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C 150 - 999 Temperature accuracy °F 17 Temperature stability °C 150 - 999 150 - 9	
Temperature range (depends on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C Temperature stability °F Temperature stability °F	
on tool) °C Temperature range (depends on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C Temperature stability °F ±17 Temperature stability °F ±4	
on tool) °F Temperature accuracy °C Temperature accuracy °F Temperature stability °C the stability °C the stability °F the stability °F the stability °F the stability °F	
Temperature accuracy °F ±17 Temperature stability °C ±2 Temperature stability °F ±4	
Temperature stability °C ±2 Temperature stability °F ±4	
Temperature stability °F ±4	
Equipotential bonding Via 3,5 mm pawl socket on front of device	
Display Backlit LCD	
Air consumption I/min	
Operating pressure	
Capacity I/min	
Vacuum	

Owning the bench









Weller Tools GmbH Carl-Benz-Straße 2 74354 Besigheim Germany

Phone: +49 (0) 7143 / 580-0 Fax.: +49 (0) 7143 / 580-108 Email: info@weller-tools.com Web: www.weller-tools.com