



SKU: 612-0011

## **Stainless Steel General Purpose Trolley**

## **DESCRIPTION:**

The serving trolleys are manufactured from high-quality stainless steel.

Rugged construction made from two tubular steel bar push handles, Ø 25 mm, with welded deep drawn shelves with elevated perimeter flange in-between. Deposit surface with large radii for easy cleaning, lowered by approx. 10 mm in contrary to the perimeter flange.

Shelves are bevelled by 35 mm all over, with flat safety return to the inside and sound absorbing lining. The trolley is protected from damage by four disc bumpers which are fixed directly above the castors. Disc bumpers are made from elastic and shock resistant plastic material. If necessary they can be exchanged easily by releasing the castors.

Corrosion-protected and maintenance-free castors. Housings made from zinc-chrome plated steel, solid castor made from impact-proof, accident grease-proof plastic, tyres from thermoplastic rubber. High-grade bearing by slide-bearings. 4 swivel castors, Ø 125 mm, 2 with brake.

If necessary the castors can be exchanged easily, pin fixing. Optionally and for additional price the trolleys can also be equipped with 2 fixed and 2 swivel castors.

## **FEATURES and BENEFITS:**

- Two shelves
- 304 grade stainless steel
- 40kg payload per shelf
- Overall dimensions: 895mm x 595mm x 960mm
- Shelf size 800mm x 500mm
- Number of shelves: 2
- Shelf dimensions in mm: 600 x 400
- Load per unit area / shelf: 40kg
- Working height between shelves in mm: 538
- Height of top shelf in mm: 800
- Total load capacity: 80kg
- Net weight: 11kg
- External dimensions W x D x H in mm: 695 x 495 x 892
- Chassis:4 swivel castors, 2 of them with brake, Ø 125mm



PRODUCT CODE	DESCRIPTION	OVERALL SIZE (inches)	OVERALL SIZE (mm)	ADDITIONAL NOTES
612-0011	Stainless Steel General Purpose Trolley	35 x 23 x 38	895 x 595 x 960	Each





