



TECHNICAL DATASHEET

ESD Protection Solutions



SKU: EP0205022

MULTI MOUNT MONITOR

Permanent workstation monitor with a multitude of functions for a single-workstation. The monitor permanently observes the correct grounding of the wrist strap and the ESD-workstation. Should either connection accidentally be disconnected (wrist strap is being taken off or the ground connection to the table mat ripped off) a acoustic and visual alarm will sound.

FEATURES:

- Improved alarm, adjustable quiet/loud
- External alarm sensor optionally available
- Non-marking
- For areas without table mats the monitoring function can be deactivated

SCOPE OF SUPPLY:

- Multi-Mount monitor
- Connection cable for table mat
- DK10 adapter for park position
- DK10 adapter for wrist strap
- Power supply 24V DC



TECHNICAL SPECIFICATIONS:

POWER SUPPLY	Input: 240-100V AC, 60/50Hz Output: 24V DC, 150 mA
SURFACE (TABLE-MAT) LIMIT	500 KΩ (±%10)
SURFACE (TABLE-MAT) TEST VOLTAGE	5V to 7.5V
WRIST STRAP MEASUREMENT RANGE	500 KΩ to 10MΩ
WRIST STRAP TEST VOLTAGE	1.2V peak-to-peak @ 1.2µA
ALARM DELAY	<50 ms
WEIGHT	0.06 KG
MEASUREMENT	45x27x20MM