

## DATASHEET

 <p><b>ESD Safety</b></p>	<div style="display: flex; justify-content: space-around;"> <div style="text-align: center;">  <p>1119</p> </div> <div style="text-align: center;">  <p>1120</p> </div> </div> <div style="text-align: center; margin-top: 20px;">  <p>1121</p> </div>
<p><b>ESD FLOORING ROLLS</b></p> <p>SKU: PLEASE REFER TO PICTURE</p>	

## PRODUCT INFORMATION

Item	Standard	Result
Thickness	ISO24346-EN430	2.00 mm
Width	024341-EN426SJ-T11236-20	2m
Length	024341-EN426SJ-T11236-20	20m
Electric Resistance	DIN51953 SJ/T11236-2001	Static Dissipative: $1.0 \times 10^6 - 1.0 \times 10^9$ ohm Conductive $< 1.0 \times 10^6$ ohm
Decay Period of Static Voltage	SJ/T10694-2006	$\leq 2$ s
Starting Voltage	SJ/T11236-2001	$ VI  < 100$ v
Amount of Wear	SJ/T11236-2001	$\leq 0.02$ gr/cm <sup>3</sup>
Combustion Properties	GB86247-2006	BF1-S1,T1
Smoke Toxicity	GB86247-2006	ZA3
Smoke Production	GB86247-2006	$\leq 750\%$ ,min
Anti-Bacterial	ISO22196	Anti-Bacterial I
Slip Resistance	DIN51130	R9
Toxic Testing	GB18586-2001	Suitable
Formaldehyde Emission	ES717-1	Without N.D
Residual Indentation	EN433	$\leq 0.10$ mm
Effect of Caster Chair	EN425	No Delamination, No Crack
Dimensional Stability	EN434	$\leq 0.40\%$
Color Fastness	ENISO 105 B02	$\geq 6$
Impact Sound Absorption	ENISO 0717/2	Approximately 2db
Resistance to Staining	EN423:2001	Not Effected



## DATASHEET

You can see the project result pictures for Article No. 1119 below;



**WIDA GENERAL TRADING L.L.C**  
ADDRESS: NO. 201 GREEN CORNER BLDG.  
AL JAZEIRA ST., AL RIGGA RD.  
DUBAI, PO BOX 171315  
UNITED ARAB EMIRATES  
PHONE: +971 4 2959818  
FAX: +971 4 2501223  
E-MAIL: SALES@WIDACO.COM



Weller



Erem



Xcelite



STANNOL



Saha



MECHATRONIC SYSTEMS



Vision ENGINEERING



VIKING



ESD Safe Equipment