

## DATASHEET



### MULTI MOUNT MONITOR

SKU: EP0205022



## PRODUCT INFORMATION

Permanent workstation monitor with a multitude of functions for a single-workstation. The monitor permanently observes the correct grounding of the wrist strap and the ESD-workstation. Should either connection accidentally be disconnected (wrist strap is being taken off or the ground connection to the table mat ripped off) a acoustic and visual alarm will sound.

### FEATURES

- Improved alarm, adjustable quiet/loud
- External alarm sensor optionally available
- Non-marking
- For areas without table mats the monitoring function can be deactivated

### TECHNICAL SPECIFICATIONS

|                                   |   |
|-----------------------------------|---|
| POWER SUPPLY:                     | Input: 100-240V AC, 50/60Hz<br>Output: 24V DC, 150 mA |
| SURFACE (TABLE-MAT) LIMIT:        | 500 K $\Omega$ ( $\pm 10\%$ )                         |
| SURFACE (TABLE-MAT) TEST VOLTAGE: | 5V to 7.5V  |
| WRIST STRAP MEASUREMENT RANGE:    | 500 K $\Omega$ to 10M $\Omega$                        |
| WRIST STRAP TEST VOLTAGE:         | 1.2V peak-to-peak @ 1.2 $\mu$ A                       |
| ALARM DELAY:                      | <50 ms  |
| WEIGHT:                           | 0.06 KG   |
| MEASUREMENT:                      | 45x27x20MM  |



Weller



Erem



Xcelite



STANNOL



Seho



MECHATRONIC  
SYSTEMS



Vision  
ENGINEERING



VIKING



ESD Safe Equipment

## DATASHEET

### SCOPE OF SUPPLY

- Multi-Mount monitor
- Connection cable for table mat
- DK10 adapter for park position
- DK10 adapter for wrist strap
- Power supply 24V DC
- Press clamp for table mat connection
- Fastening screws
- Calibration certificate



Weller



Erem  
Weller



Xcelite  
Weller



STANNOL



Seho



MECHATRONIC  
SYSTEMS



Vision  
ENGINEERING



VIKING



ESD Safe Equipment