

DATASHEET



ESD Safety

PINK POLY ANTISTATIC TUBING

SKU: PLEASE REFER TO THE TABLE



PRODUCT INFORMATION

Pink poly antistatic tubing rolls are manufactured as per IEC 61340-5-1 and 94/62/EC & 2002/95/EC (ROHS directives) standards.

FEATURES AND BENEFITS

- Material: Pink Polyethylene with Antistatic Agent
- Thickness: 90μ (+/- 10%)
- Surface Resistance: <math><10^{11}</math> Ohm
- Decay Time: from 1000V to 100V < 2 seconds
- Roll Length: 250m

DIMENSIONS & PART NUMBERS

Art. No.	Dimensions
PK000012	100MMX250M
PK000013	150MMX250M
PK000014	250MMX250M
PK000015	300MMX250M
PK000016	400MMX250M
PK000017	500MMX250M

WIDA GENERAL TRADING L.L.C

ADDRESS: DUBAI, PO BOX 171315

UNITED ARAB EMIRATES

PHONE: +971 4 2959818

WWW.WODACO.NET

E-MAIL: SALES@WIDACO.COM



Weller



Erem



Xcelite



STANNOL



Setho



MECHATRONIC SYSTEMS



Vision ENGINEERING



VIKING



ESD Safe Equipment