

2-Channel Power Unit, 200 W (255 W)

Item No: T0053421399N



KEY FEATURES

- + Power unit WX 2, with 2 channels, 2 soldering irons WXP 120 and 2 safety rests WDH 10
- + Robust touch screen with ESD safe glass
- + Intuitive use with turn-click-wheel with enter key and finger guide.
- + Blue LED backlighting
- + Multilingual menu navigation
- + High functionality
- + No safety rest with Stop & Go function needed thanks to integrated acceleration sensor
- + Optimized precision, better stability by sensor in the soldering iron
- + Specific parameterization of tool by storage medium in hand piece
- + Visual process control via blue LED ring light

TECHNICAL DATA

Width	154.0 mm
Height	135.0 mm
Length	174.0 mm
Dimensions L x W x H	174.0 x 154.0 x 135.0mm
Automatic Tool Identification	Yes
Benchtop Controller	Yes
Equipotential Bonding	Yes
Equipotential Bonding Socket	Via 3,5 mm pawl socket on back of device
ESD Safe	Yes
Fuse	T2A
Interface	1x USB, 2x RS232, 1x Switching Output
Multilingual Display	Yes
Number of Channels	2
Temperature Accuracy °F	±9 °C
Temperature Range °C	100 - 550 °C
Temperature Stability °F	±2 °C
Traceability	Yes