



2-Channel Power Unit, 200 W (255 W)

Item No: T0053426399N

2-Channel Power Unit, 200 W (255 W)

KEY FEATURES

- + Cost effective because only one station is needed
- + Less rework by optimal use of tools and the correct working temperature. Reduction of running costs by longer tip lifetime.
- + Desoldering iron with stand-by mode
- + ESD safe
- + For operation with external compressed air

TECHNICAL DATA

| | |
|-------------------------------|-------------------------|
| Width | 154.0 mm |
| Height | 135.0 mm |
| Length | 174.0 mm |
| Dimensions L x W x H | 174.0 x 154.0 x 135.0mm |
| Air Consumption | 35 l/min |
| Air Pressure | 58 - 87 psi |
| Automatic Tool Identification | Yes |

| | |
|--|--|
| Benchtop Controller | Yes |
| Compressed Air Connection (Outer Diameter) | 6.0mm |
| Compressed Air Connection Accessory | Oil free, dry compressed air |
| Desoldering | Yes |
| Equipotential Bonding | Yes |
| Equipotential Bonding Socket | Via 3,5 mm pawl socket on back of unit. |
| ESD Safe | Yes |
| Fuse | T2A |
| Interface | 1x USB, 2x RS232, 1x Switching Output |
| IPC Compliant | Yes |
| Maximum Volume | 0.7 bar |
| Multilingual Display | Yes |
| Number of Channels | 2 |
| Operating Pressure | 4 - 6 bar 54 - 87 psi |
| Power | 200 W (255 W |
| Temperature Accuracy °C | ± 9 °C |
| Temperature Accuracy °F | ±17 °C |
| Temperature Range (Depends on Tool) | 50 - 550°C |
| Temperature Stability °C | ±2 °C |
| Temperature Stability °F | ±4 °C |
| Traceability | Yes |
| USB | USB interface of firmware updates, parameterization and monitoring USB interface supports all standard USB flash drive types |
| Vacuum | 0.5 bar (55 kPA) (8 psi) |
| Voltage | 230 V |