



Soldering bath 150 W, 24 V

Item No: T0052704299N

Soldering bath 150 W, 24 V

KEY FEATURES

- + WSB 150 Soldering Bath 150 W, 24 V
- + Connectable to all Weller 150 W digital stations and WR3M
- + For tin coating and preparation of electronics components and leads
- + Precision temperature control / 150° F - 850° F / 50° C - 454° C
- + Heated surface - 150 W: Soldering bath - 2.3"; x 1.2"; x 0.75"; / 58 mm x 30 mm x 19 mm
- + For lead free solder
- + Heat-up time ~ 10 min (50°C - 350°C)
- + For lead free solder

TECHNICAL DATA

| | |
|---|------------------------|
| Width | 120.0 mm |
| Height | 54.0 mm |
| Length | 175.0 mm |
| Dimensions L x W x H | 175.0 x 120.0 x 54.0mm |
| Approximate Heating Time (50-350 °C/120-660 °F) | 660 sec |
| ESD Safe | Yes |
| Power | 150 W |
| Soldering Bath Dimensions (L x W x H) | 57.9 x 33.0 x 19.0mm |
| Temperature Range (Depends on Tool) | 65 - 454°C |
| Temperature Range °C | 65 - 454 °C |
| Temperature Range °F | 149 - 849 °F |
| Tip Type | WT |
| UPC | 037103304728 |