



TECHNICAL DATASHEET

ESD Protection Solutions

SKU: Refer to the below table

Kapton Tape 6~40mm x 33m 260°C

ESD and Non-ESD Kapton tape is with polyimide film as the basic carrier, and coated with different adhesive for different temperature resistance. It features like: high temperature resistance, electrical insulation, radiation resistance, solvent resistance etc.

It's mostly applied for the motor insulation, gold finger protection of PCB during wave soldering, transformer coil wrapping, motor coil fixation, and external insulation etc.

TECHNICAL DATA:

- DuPont™ material
- High temperature resistance
- Low residue
- Standard Tape: Kapton film coated with silicone adhesive
- Antistatic Tape: Polyimide film coated with silicone adhesive designed to provide high electrostatic dissipation
- Custom sizes available on request
- Total Thickness: 0.06 mm
- Length: 33 m
- Operating Temperature: 260°C
- Adhesive: Silicone
- Backing/Carrier: Polyimide
- Color: Amber





TECHNICAL DATASHEET

ESD Protection Solutions

PRODUCT CODE	DESCRIPTION	ESD SAFE
W00157-06	Kapton Tape 6mm x 33m 260°C	YES
W00157-09	Kapton Tape 9mm x 33m 260°C	YES
W00157-12	Kapton Tape 12mm x 33m 260°C	YES
W00157-15	Kapton Tape 15mm x 33m 260°C	YES
W00157-19	Kapton Tape 19mm x 33m 260°C	YES
W00157-22	Kapton Tape 22mm x 33m 260°C	YES
W00157-25	Kapton Tape 25mm x 33m 260°C	YES
W00157-40	Kapton Tape 40mm x 33m 260°C	YES
W00257-06	Kapton Tape 6mm x 33m 260°C	NO
W00257-09	Kapton Tape 9mm x 33m 260°C	NO
W00257-12	Kapton Tape 12mm x 33m 260°C	NO
W00257-15	Kapton Tape 15mm x 33m 260°C	NO
W00257-19	Kapton Tape 19mm x 33m 260°C	NO
W00257-22	Kapton Tape 22mm x 33m 260°C	NO
W00257-25	Kapton Tape 25mm x 33m 260°C	NO