



CONSTRUCT Offshore

01-010906H

Safety boots equipped with innovative, waterproof membrane and Thinsulate 3M insulation. The shoes have a heat-resistant PU / Rubber sole with a self-cleaning tread. Reflective elements increase work safety in darkened rooms and outdoors



Brand	PROTEKTOR
Industry	Construction / Finishing works, Firefighter and medical rescue, Heavy industry
Product type	Ankle boots
Color	● Black
Norm	EN ISO 20345:2011
Certificate	IPS-1439-7/2022 edition1
Product features	increased durability of the upper, composite toe cap, metal free, easy-clean upper, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, reflective elements, bellows tongue, insulated, disinfection, PRO-TENDON technology (Achilles tendon protection), COLD PROTECTION technology
Product characteristics	<p>increased water resistance</p> <p>lining - waterproof, vapor-permeable membrane</p> <p>increased upper strength</p> <p>grain leather - excellent tensile strength parameters, a minimum of 15 N/mm² is required and our result is 29.1 N/mm²</p> <p>outsole - increased abrasion resistance required result in the standard: less than or equal to 150 mm³ - our result 70 mm³, energy absorption in the heel area according to the standard minimum 20J, our result 30.6J</p> <p>resistance of the outsole to acids</p> <p>heat-resistant outsole (resistant to contact with 300°C for 60 seconds)</p> <p>outsole - protection against ankle sprains, thanks to the increased stability provided by the extended heel area - up to 92 mm wide in size 42</p> <p>outsole design for easy removal using the "shoe against shoe" method</p>
Upper material	Grain leather
Lining & Sock	Technological fabric, membrane lining
Insole	Fabric, replaceable insole
Sole	Pu/Rubber, heat-resistant sole, sole tread allowing climbing the ladder safely, resistance to acids, PRT FLEX technology, SHOCK ABSORBER technology, ANA-TECH technology (extended heel surface in the sole), SELF CLEAN technology (self-cleaning sole)
Fastener type	Shoelaces
Fit type	H 1/2
Available sizes	FR 35-50 CM 22,5-32,5 UK 3-14,5
Weight (half pair s.42) +/- 3% t.	0,85 kg