

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 1 of 8

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Graphite

1.2. Relevant identified uses of the substance or mixture and uses advised against

Uses advised against

Reserved for industrial and professional use.

1.3. Details of the supplier of the safety data sheet

Company name: ITW LLC & Co. KG
Street: Mühlackerstrasse 149
Place: D-75417 Mühlacker
Telephone: ++49(0)7041-96340 Telefax: ++49(0)7041-963429
e-mail: info@itwcp.de
Internet: www.itwcp.de
Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00
Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in Switzerland dial 145)
United Kingdom : National Poisons Information Service - Phone number : 8448920111
Österreich : Vergiftungsinformationszentrale Vienna - Telefon-Nummer : +43 1 406 43 43
Schweiz : Tox Info Suisse - Telefon-Nummer : +41 44 251 51 51
Italia : Centro Antiveleni, Roma - Numero di telefono : +39 06 305 4343
España : Instituto Nacional de Toxicología - Teléfono : +34 91 562 04 20
Deutschland: ++49(0)7041-96340

1.4. Emergency telephone number:

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

Regulation (EC) No. 1272/2008

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Specific target organ toxicity - single exposure: STOT SE 3

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

May cause drowsiness or dizziness.

2.2. Label elements

Regulation (EC) No. 1272/2008

Hazard components for labelling

n-butyl acetate, Acetone, Isopropanol

Signal word: Danger

Pictograms:



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 2 of 8

Hazard statements

| | |
|------|---|
| H222 | Extremely flammable aerosol. |
| H229 | Pressurised container: May burst if heated. |
| H319 | Causes serious eye irritation. |
| H336 | May cause drowsiness or dizziness. |

Precautionary statements

| | |
|----------------|--|
| P211 | Do not spray on an open flame or other ignition source. |
| P410+P412 | Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F. |
| P251 | Do not pierce or burn, even after use. |
| P271 | Use only outdoors or in a well-ventilated area. |
| P305+P351+P338 | IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. |

Special labelling of certain mixtures

| | |
|--------|---|
| EUH066 | Repeated exposure may cause skin dryness or cracking. |
|--------|---|

SECTION 3: Composition/information on ingredients

3.2. Mixtures

Hazardous components

| CAS No | Chemical name | | | Quantity |
|----------|---|--------------|----------|----------|
| | EC No | Index No | REACH No | |
| | GHS Classification | | | |
| 123-86-4 | n-butyl acetate | | | 25-50% |
| | 204-658-1 | 607-025-00-1 | | |
| | Flam. Liq. 3, STOT SE 3; H226 H336 EUH066 | | | |
| 67-63-0 | propan-2-ol; isopropyl alcohol; isopropanol | | | 5-20% |
| | 200-661-7 | 603-117-00-0 | | |
| | Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336 | | | |
| 106-97-8 | butane | | | 10-25% |
| | 203-448-7 | 601-004-00-0 | | |
| | Flam. Gas 1; H220 | | | |
| 74-98-6 | propane | | | 10-25% |
| | 200-827-9 | 601-003-00-5 | | |
| | Flam. Gas 1; H220 | | | |

Full text of H and EUH statements: see section 16.

SECTION 4: First aid measures

4.1. Description of first aid measures

After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

After ingestion

If swallowed, immediately drink: Water.

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 3 of 8

4.2. Most important symptoms and effects, both acute and delayed

No data available

4.3. Indication of any immediate medical attention and special treatment needed

No data available

SECTION 5: Firefighting measures**5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO₂). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

5.2. Special hazards arising from the substance or mixture

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

5.3. Advice for firefighters

In case of fire: Wear self-contained breathing apparatus.

Additional information

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

SECTION 6: Accidental release measures**6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

6.2. Environmental precautions

Do not allow to enter into surface water or drains. Explosion hazard.

6.3. Methods and material for containment and cleaning up

Ventilate affected area.

SECTION 7: Handling and storage**7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Advice on protection against fire and explosion

Keep away from sources of ignition - No smoking.

7.2. Conditions for safe storage, including any incompatibilities**Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

Hints on joint storage

Do not store together with: Material, rich in oxygen, oxidizing.

SECTION 8: Exposure controls/personal protection**8.1. Control parameters**

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 4 of 8

Exposure limits (EH40)

| CAS No | Substance | ppm | mg/m ³ | fibres/ml | Category | Origin |
|----------|---------------|-----|-------------------|-----------|---------------|--------|
| 106-97-8 | Butane | 600 | 1450 | | TWA (8 h) | WEL |
| | | 750 | 1810 | | STEL (15 min) | WEL |
| 123-86-4 | Butyl acetate | 150 | 724 | | TWA (8 h) | WEL |
| | | 200 | 966 | | STEL (15 min) | WEL |
| 67-63-0 | Propan-2-ol | 400 | 999 | | TWA (8 h) | WEL |
| | | 500 | 1250 | | STEL (15 min) | WEL |

8.2. Exposure controls



Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

Eye/face protection

Tightly sealed safety glasses.

Hand protection

DIN EN 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

Skin protection

Protective clothing:

Respiratory protection

In case of inadequate ventilation wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

| | |
|-----------------|----------------|
| Physical state: | Aerosol |
| Colour: | black |
| Odour: | characteristic |

Changes in the physical state

| | |
|--|------------|
| Initial boiling point and boiling range: | -0,5 °C |
| Flash point: | <0 °C |
| Lower explosion limits: | 1,4 vol. % |
| Upper explosion limits: | 9,4 vol. % |
| Ignition temperature: | 365 °C |
| Vapour pressure: (at 20 °C) | 2100 hPa |
| Vapour pressure: (at 50 °C) | 4900 hPa |

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 5 of 8

Density (at 20 °C):

0,88 g/cm³**SECTION 10: Stability and reactivity****10.1. Reactivity**

No data available

10.2. Chemical stability

No data available

10.3. Possibility of hazardous reactions

No data available

10.4. Conditions to avoid

Keep away from heat. Ignition hazard.

10.5. Incompatible materials

No data available

10.6. Hazardous decomposition products

No data available

SECTION 11: Toxicological information**11.1. Information on toxicological effects****Acute toxicity**

| CAS No | Chemical name | | | | |
|----------|----------------------|-------------|---------|--------|--------|
| | Exposure route | Dose | Species | Source | Method |
| 106-97-8 | butane | | | | |
| | inhalation (4 h) gas | LC50 ppm | 273000 | Rat | GESTIS |

Irritation and corrosivity

Irritating to eyes. Vapours may cause drowsiness and dizziness.

STOT-repeated exposure

Has degreasing effect on the skin. Frequently or prolonged contact with skin may cause dermal irritation.

SECTION 12: Ecological information**12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

| CAS No | Chemical name | Log Pow |
|----------|---------------|---------|
| 106-97-8 | butane | 2,89 |
| 74-98-6 | propane | 2,36 |

Further information

Do not allow to enter into surface water or drains.

SECTION 13: Disposal considerations**13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.

Waste disposal number of waste from residues/unused products

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 6 of 8

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

Waste disposal number of contaminated packaging

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

Contaminated packaging

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

SECTION 14: Transport information**Land transport (ADR/RID)**

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 625
Limited quantity: 1 L
Transport category: 2
Tunnel restriction code: D

Other applicable information (land transport)

E0

Inland waterways transport (ADN)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
Hazard label: 2.1



Classification code: 5F
Special Provisions: 190 327 344 625
Limited quantity: 1 L

Other applicable information (inland waterways transport)

E0

Marine transport (IMDG)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS
14.3. Transport hazard class(es): 2
14.4. Packing group: -
Hazard label: 2, see SP63

Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 7 of 8

Special Provisions: 63, 190, 277, 327, 344, 959
Limited quantity: See SP277
EmS: F-D, S-U

Other applicable information (marine transport)

E0

Air transport (ICAO-TI/IATA-DGR)

14.1. UN number: UN1950
14.2. UN proper shipping name: AEROSOLS, flammable
14.3. Transport hazard class(es): 2.1
Hazard label: 2.1



Special Provisions: A145 A167
Limited quantity Passenger: 30 kg G
IATA-packing instructions - Passenger: 203
IATA-max. quantity - Passenger: 75 kg
IATA-packing instructions - Cargo: 203
IATA-max. quantity - Cargo: 150 kg

Other applicable information (air transport)

E0

: Y203

14.5. Environmental hazards

ENVIRONMENTALLY HAZARDOUS: no

SECTION 15: Regulatory information**15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: butane

2004/42/EC (VOC): 16,67 % (146,696 g/l)

National regulatory information

Water contaminating class (D): 1 - slightly water contaminating

SECTION 16: Other information**Relevant H and EUH statements (number and full text)**

H220 Extremely flammable gas.
H222 Extremely flammable aerosol.
H225 Highly flammable liquid and vapour.
H226 Flammable liquid and vapour.
H229 Pressurised container: May burst if heated.
H319 Causes serious eye irritation.
H336 May cause drowsiness or dizziness.
EUH066 Repeated exposure may cause skin dryness or cracking.



Safety Data Sheet

according to Regulation (EC) No 1907/2006

Graphite

Revision date: 16.10.2019

Product code: 128

Page 8 of 8

(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)