

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Antistatik**

Revision date: 02.12.2019

Product code: 133

Page 1 of 7

**SECTION 1: Identification of the substance/mixture and of the company/undertaking****1.1. Product identifier**

Antistatik

**1.2. Relevant identified uses of the substance or mixture and uses advised against****Uses advised against**

Reserved for industrial and professional use.

**1.3. Details of the supplier of the safety data sheet**

Company name: ITW LLC & Co. KG  
Street: Mühlackerstrasse 149  
Place: D-75417 Mühlacker  
Telephone: ++49(0)7041-96340      Telefax: ++49(0)7041-963429  
e-mail: info@itwcp.de  
Internet: www.itwcp.de  
Responsible Department: Produktsicherheit Mo. - Do. 8.00 - 16.30 Fr. 8.00 - 14.00  
Swiss Toxicological Information Centre - Téléphone : +41 44 251 51 51 (in Switzerland dial 145)  
United Kingdom : National Poisons Information Service - Phone number : 8448920111  
Österreich : Vergiftungsinformationszentrale Vienna - Telefon-Nummer : +43 1 406 43 43  
Schweiz : Tox Info Suisse - Telefon-Nummer : +41 44 251 51 51  
Italia : Centro Antiveleni, Roma - Numero di telefono : +39 06 305 4343  
España : Instituto Nacional de Toxicología - Teléfono : +34 91 562 04 20  
Deutschland: ++49(0)7041-96340

**1.4. Emergency telephone number:****SECTION 2: Hazards identification****2.1. Classification of the substance or mixture****Regulation (EC) No. 1272/2008**

Hazard categories:

Aerosol: Aerosol 1

Serious eye damage/eye irritation: Eye Irrit. 2

Hazard Statements:

Extremely flammable aerosol.

Pressurised container: May burst if heated.

Causes serious eye irritation.

**2.2. Label elements****Regulation (EC) No. 1272/2008****Hazard components for labelling**

Isopropanol

**Signal word:** Danger**Pictograms:****Hazard statements**

H222

Extremely flammable aerosol.

H229

Pressurised container: May burst if heated.

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Antistatik

Revision date: 02.12.2019

Product code: 133

Page 2 of 7

H319 Causes serious eye irritation.

#### Precautionary statements

P410+P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/122 °F.  
 P102 Keep out of reach of children.  
 P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 P261 Avoid breathing dust/fume/gas/mist/vapours/spray.  
 P271 Use only outdoors or in a well-ventilated area.  
 P251 Do not pierce or burn, even after use.  
 P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.

### SECTION 3: Composition/information on ingredients

#### 3.2. Mixtures

##### Hazardous components

CAS No	Chemical name			Quantity
	EC No	Index No	REACH No	
	GHS Classification			
75-28-5	isobutane			25-50%
	200-857-2	601-004-00-0		
	Flam. Gas 1; H220			
74-98-6	propane			25-50%
	200-827-9	601-003-00-5		
	Flam. Gas 1; H220			
67-63-0	propan-2-ol; isopropyl alcohol; isopropanol			10-25%
	200-661-7	603-117-00-0		
	Flam. Liq. 2, Eye Irrit. 2, STOT SE 3; H225 H319 H336			
106-97-8	butane			2,5-10%
	203-448-7	601-004-00-0		
	Flam. Gas 1; H220			

Full text of H and EUH statements: see section 16.

### SECTION 4: First aid measures

#### 4.1. Description of first aid measures

##### After inhalation

Provide fresh air. In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

##### After contact with skin

After contact with skin, wash immediately with: Water. Change contaminated clothing.

##### After contact with eyes

If product gets into the eye, keep eyelid open and rinse immediately with large quantities of water, for at least 5 minutes. Subsequently consult an ophthalmologist.

##### After ingestion

If swallowed, immediately drink: Water.

#### 4.2. Most important symptoms and effects, both acute and delayed

No data available

#### 4.3. Indication of any immediate medical attention and special treatment needed

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Antistatik**

Revision date: 02.12.2019

Product code: 133

Page 3 of 7

No data available

**SECTION 5: Firefighting measures****5.1. Extinguishing media****Suitable extinguishing media**Carbon dioxide (CO<sub>2</sub>). Foam. Extinguishing powder.**Unsuitable extinguishing media**

Water with tenside additive. Water.

**5.2. Special hazards arising from the substance or mixture**

Combustible. Vapours may form explosive mixtures with air. Heating causes rise in pressure with risk of bursting.

**5.3. Advice for firefighters**

In case of fire: Wear self-contained breathing apparatus.

**Additional information**

Use water spray jet to protect personnel and to cool endangered containers. Suppress gases/vapours/mists with water spray jet.

**SECTION 6: Accidental release measures****6.1. Personal precautions, protective equipment and emergency procedures**

Remove all sources of ignition. Provide adequate ventilation. Wear a self-contained breathing apparatus and chemical protective clothing.

**6.2. Environmental precautions**

Do not allow to enter into surface water or drains. Explosion hazard.

**6.3. Methods and material for containment and cleaning up**

Ventilate affected area.

**SECTION 7: Handling and storage****7.1. Precautions for safe handling****Advice on safe handling**

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

**Advice on protection against fire and explosion**

Keep away from sources of ignition - No smoking.

**7.2. Conditions for safe storage, including any incompatibilities****Requirements for storage rooms and vessels**

Keep container tightly closed. Keep in a cool, well-ventilated place. Keep away from sources of ignition - No smoking.

**Hints on joint storage**

Do not store together with: Material, rich in oxygen, oxidizing.

**SECTION 8: Exposure controls/personal protection****8.1. Control parameters**

## Safety Data Sheet

according to Regulation (EC) No 1907/2006

### Antistatik

Revision date: 02.12.2019

Product code: 133

Page 4 of 7

#### Exposure limits (EH40)

CAS No	Substance	ppm	mg/m <sup>3</sup>	fibres/ml	Category	Origin
106-97-8	Butane	600	1450		TWA (8 h)	WEL
		750	1810		STEL (15 min)	WEL
67-63-0	Propan-2-ol	400	999		TWA (8 h)	WEL
		500	1250		STEL (15 min)	WEL

#### 8.2. Exposure controls



##### Appropriate engineering controls

If handled uncovered, arrangements with local exhaust ventilation have to be used. Do not breathe gas/fumes/vapour/spray.

##### Protective and hygiene measures

Remove contaminated, saturated clothing immediately. Protect skin by using skin protective cream. After work, wash hands and face. When using do not eat or drink.

##### Eye/face protection

Tightly sealed safety glasses.

##### Hand protection

DIN EN 374 Tested protective gloves are to be worn: NBR (Nitrile rubber) For special purposes, it is recommended to check the resistance to chemicals of the protective gloves mentioned above together with the supplier of these gloves. NBR (Nitrile rubber)

##### Skin protection

Protective clothing:

##### Respiratory protection

In case of inadequate ventilation wear respiratory protection.

## SECTION 9: Physical and chemical properties

### 9.1. Information on basic physical and chemical properties

Physical state:	Aerosol
Colour:	colourless
Odour:	characteristic

#### Changes in the physical state

Initial boiling point and boiling range:	-0,5 °C
Flash point:	<0 °C
Sustaining combustion:	Not sustaining combustion
Ignition temperature:	365 °C
Density (at 20 °C):	0,59 g/cm <sup>3</sup>

## SECTION 10: Stability and reactivity

### 10.1. Reactivity

No data available

### 10.2. Chemical stability

No data available

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Antistatik**

Revision date: 02.12.2019

Product code: 133

Page 5 of 7

**10.3. Possibility of hazardous reactions**

No data available

**10.4. Conditions to avoid**

Keep away from heat. Ignition hazard.

**10.5. Incompatible materials**

No data available

**10.6. Hazardous decomposition products**

No data available

**SECTION 11: Toxicological information****11.1. Information on toxicological effects****Acute toxicity**

CAS No	Chemical name					
	Exposure route	Dose	Species	Source	Method	
106-97-8	butane					
	inhalation (4 h) gas	LC50 ppm	273000	Rat	GESTIS	

**Irritation and corrosivity**

Irritating to eyes. Vapours may cause drowsiness and dizziness.

**SECTION 12: Ecological information****12.3. Bioaccumulative potential****Partition coefficient n-octanol/water**

CAS No	Chemical name	Log Pow
75-28-5	isobutane	2,8
74-98-6	propane	2,36
106-97-8	butane	2,89

**Further information**

Do not allow to enter into surface water or drains.

**SECTION 13: Disposal considerations****13.1. Waste treatment methods****Advice on disposal**

Dispose of waste according to applicable legislation.

**Waste disposal number of waste from residues/unused products**

160504 WASTES NOT OTHERWISE SPECIFIED IN THE LIST; gases in pressure containers and discarded chemicals; gases in pressure containers (including halons) containing hazardous substances; hazardous waste

**Waste disposal number of contaminated packaging**

150104 WASTE PACKAGING; ABSORBENTS, WIPING CLOTHS, FILTER MATERIALS AND PROTECTIVE CLOTHING NOT OTHERWISE SPECIFIED; packaging (including separately collected municipal packaging waste); metallic packaging

**Contaminated packaging**

Non-contaminated packages may be recycled. Handle contaminated packages in the same way as the substance itself.

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Antistatik**

Revision date: 02.12.2019

Product code: 133

Page 6 of 7

**SECTION 14: Transport information****Land transport (ADR/RID)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 625  
Limited quantity: 1 L  
Transport category: 2  
Tunnel restriction code: D

**Other applicable information (land transport)**

E0

**Inland waterways transport (ADN)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
Hazard label: 2.1



Classification code: 5F  
Special Provisions: 190 327 344 625  
Limited quantity: 1 L

**Other applicable information (inland waterways transport)**

E0

**Marine transport (IMDG)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS  
**14.3. Transport hazard class(es):** 2  
**14.4. Packing group:** -  
Hazard label: 2, see SP63

Special Provisions: 63, 190, 277, 327, 344, 959  
Limited quantity: See SP277  
EmS: F-D, S-U

**Other applicable information (marine transport)**

E0

**Air transport (ICAO-TI/IATA-DGR)**

**14.1. UN number:** UN1950  
**14.2. UN proper shipping name:** AEROSOLS, flammable

**Safety Data Sheet**

according to Regulation (EC) No 1907/2006

**Antistatik**

Revision date: 02.12.2019

Product code: 133

Page 7 of 7

**14.3. Transport hazard class(es):**

2.1

Hazard label:

2.1



Special Provisions:

A145 A167

Limited quantity Passenger:

30 kg G

IATA-packing instructions - Passenger:

203

IATA-max. quantity - Passenger:

75 kg

IATA-packing instructions - Cargo:

203

IATA-max. quantity - Cargo:

150 kg

**Other applicable information (air transport)**

E0

: Y203

**14.5. Environmental hazards**

ENVIRONMENTALLY HAZARDOUS: no

**SECTION 15: Regulatory information****15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture****EU regulatory information**

Restrictions on use (REACH, annex XVII):

Entry 28: isobutane; butane

2004/42/EC (VOC):

7,41 % (43,719 g/l)

**National regulatory information**

Water contaminating class (D):

1 - slightly water contaminating

**SECTION 16: Other information****Relevant H and EUH statements (number and full text)**

H220	Extremely flammable gas.
H222	Extremely flammable aerosol.
H225	Highly flammable liquid and vapour.
H229	Pressurised container: May burst if heated.
H319	Causes serious eye irritation.
H336	May cause drowsiness or dizziness.

*(The data for the hazardous ingredients were taken respectively from the last version of the sub-contractor's safety data sheet.)*