



Technical Data Sheet

CRAMOLIN® PROTECTION Art. No. 115

Product description

PROTECTION contains a combination of high-quality active ingredients ensuring long-time protection of metallic contacts from abrasion and corrosion. Treated contacts are coated with a stable and superfine film that gives excellent lubricating and corrosion protection. PROTECTION is suitable for contact metals of all kinds and does not attack any common used engineering material. It retains its effectiveness within a wide range of temperatures and is non-toxic.

Application

PROTECTION is suitable for all electronic equipment and appliances for the prevention of malfunctions caused by corroded contacts. It reduces noticeably the abrasion of contacts and accordingly prolongs their service life. PROTECTION has been used successfully in production as well as in maintenance and repair work.

Please note

Shake can well before use. Spray thoroughly on parts to be treated. For accurate work use the attached extension tube. Spray on part to be treated. For accurate work use attached extension tube. Through high capillary attraction, product also acts at places of difficult access. Oxidized or corroded contact surfaces should first be treated with CONTACTCLEAN and dissolved oxides washed off with SPRAYWASH. Do not spray on naked flame or on hot parts. Keep away from sources of ignition. No smoking during use.



Technical Data

Appearance:	bluish liquid
Density at 20° C:	0,73 [g/cm ³]
Odor:	that of alcohol
Viscosity film at 40° C:	67,4 [mm ² /s]
Pour point:	-9 [° C]
Increase of the RC-value after treatment:	1 [mΩ]
Compatibility with materials:	excellent

Storage / Shelf Life

Shelf life is 2 years if stored correctly.
Package after emptying to be disposed via metal scrap.