

# TRAX

01-025374



Brand	PROTEKTOR
Industry	Electronics industry, Light industry, Transport / Warehouses
Product type	Shoes
Color	Gray
Norm	EN ISO 20345:2011
Certificate	150/2023/PPE/1439/B wyd.1
Product features	increased breathability, composite toe cap, metal free, easy-clean upper, additional toe reinforcement in the upper, the footwear is suitable for working on the knees, disinfection
Product characteristics	<p>increased breathability</p> <p>velour - water vapour coefficient in requirements not less than 15 mg/cm<sup>2</sup> - our result 79.4 mg/cm<sup>2</sup></p> <p>lining - increased water vapour permeability required minimum 0.8 mg/ (cm<sup>2</sup>*h) - our result 42.9 mg/ (cm<sup>2</sup>*h), water vapour coefficient required minimum 15 mg/cm<sup>2</sup> - our result 343.3 mg/cm<sup>2</sup></p> <p>outsole - increased abrasion resistance required result in the standard: less than or equal to 150 mm<sup>3</sup> - our result is 24 mm<sup>3</sup></p> <p>energy absorption in the heel area according to the standard: minimum 20J, our result 27.2J</p> <p>resistance of the outsole to acids and alkalis</p> <p>resistance of the outsole to short-term contact with hot surfaces at a temperature of 180°C</p> <p>outsole - protection against ankle sprains as a result of increased stability achieved by expanding the heel area - in size 42 up to 95 mm wide</p> <p>outsole construction for easy removal using the "shoe against shoe" method</p>
Upper material	Velour leather
Lining & Sock	Technological fabric
Insole	Fabric, replaceable insole
Sole	Pu/Pu, sole tread allowing climbing the ladder safely, resistance to acids, resistance to bases, resistance to short-term contact with hot ground at 180 ° C, PRT FLEX technology, SHOCK ABSORBER technology, ANA-TECH technology (extended heel surface in the sole)
Fastener type	Shoelaces
Fit type	H 1/2
Available sizes	FR 35-51 CM 22,5-33 UK 3-15,5
Weight (half pair s.43) +/- 3% t.	0,64 kg