



SKU: 21-704-XXXX

## **CONDUCTIVE LOOSE, HINGED, SWING LATCHES LIDS**

## SPECIFICATIONS:

- Material: Conductive polypropylene (carbon-loaded)
- Colour: Black
- ESD Marking: All lids marked with ESD sign
- Surface resistance ≤ 10<sup>4</sup> ohm
- Usage temperature: 80°C. Please note that depending of load, deformation can appear from 50°C.
- Stackability: All containers may be stacked together in a wide range of configurations.
- Standard compliance: IEC 61340-5-1 RoHS Directive (2002 /95/CE)









## **WIDA GENERAL TRADING LLC**













PRODUCT CODE	DESCRIPTION	DIMENSIONS
21-704-0005	CONDUCTIVE LOOSE LID	300 X 200
21-704-0010	CONDUCTIVE LOOSE LID	400 X 300
21-704-0015	CONDUCTIVE LOOSE LID	600 X 400
21-704-0020	CONDUCTIVE HINGED LID W/ 2 SWING LATCHES LID	300 X 200
21-704-0025	CONDUCTIVE HINGED LID W/ 2 SWING LATCHES LID	400 X 300
21-704-0030	CONDUCTIVE HINGED LID W/ 2 SWING LATCHES LID	600 X 400
21-704-0035	CONDUCTIVE LID W/4 SWING LATCHES LID	300 X 200
21-704-0040	CONDUCTIVE LID W/4 SWING LATCHES LID	400 X 300
21-704-0045	CONDUCTIVE LID W/4 SWING LATCHES LID	600 X 400





